

# Cartoner



## Specifications

Machine	NSX 3.1	NSX 5.1	NSX 5.1 L
Nominal Speed dry run	Upto 130 cartons/min	Upto 130 cartons/min	Upto 200 cartons/min
Connected load	3.5kW, 415V,3Ø+N, 50Hz	3.5kW, 415V,3Ø+N, 50Hz	6kW, 415V,3Ø+N, 50Hz
Air consumption at 6 Bar	8.3 NL/Cycle	8.3 NL/Cycle	8.3 NL/Cycle
Machine size(LxWxH,mm)	4600 x 1180 x 1750	7390 x 1600 x 1750	8150 x 1890 x 1750
Machine Construction	MS Painted or SS 304	MS Painted or SS 304	MS Painted or SS 304
Synchronization with VFFS machine	not possible	possible	possible
Carton Length Size (A) (mm)	108 – 290	108 – 250	108 – 250
Carton Width Size (B)* (mm)	44 – 250	44 – 250	44 – 250
Carton Height (C)* (mm)	20 – 90	20 – 80	20 – 80

Built under the technical know-how of **Jacob White Packaging, UK**, these cartoners are suited for secondary packing of Flexible pouches, Trays, Solid bars, etc.

The cartoners can be provided with

- Ink Jet Printers, Laser Thermal Transfer And Deboss Coding
- Open Flap Detection
- Bar Code Verification & Data Collection
- Automatic Carton Feeder
- Product Transfer & Collection
- Tuck Closure
- Glue Tuck Closure

